



CONTACT US FOR MORE INFORMATON

Note: For safety, reliability and better performance of Scania vehicles, we recommend to get the service done at Scania authorized workshop and use only Scania genuine spare parts.

Scania CV India Pvt Ltd

Plot No.63 (Part), 64, 66,88-97, Narsapura KIADB Industrial Area, Achhatanahalli Village, Narsapura Hobli, Kolar District, Pin - 563 130, Karnataka, India

PPS Motors Private Limited

(Head Office)
Office No. 205,206,207,208,
M.No. 6-3-1192/1/13, 1-14, 1-19, 1-20,
2nd Block, 2nd Floor,White House, Begumpet,
Khairatabad Village, Hyderabad,
Telangana - 500016
© 93474 09068

Central Warehouse Scania CV India Pvt Ltd

Survey # 101/1, Village Nimji, Taluka Kalmeshwar, Dist. Nagpur, 441501 Maharashtra

South Zone PPS Motors Private Limited

Survey No.17,18,19,22/2 part, 34,35,36 and 38, Situated at Pedda Amberpet Village, Abudullapurmet Mandal, Rangareddy, Telangana, 501512

© Sales - 93474 09068 © Service - 93919 36711

East Zone-1PPS Motors Private Limited

Khata No. 117/258, Laband Bud Village, H.Kantapali P.O, Mouza Beherapet,

Jharsuguda, Odisha, 768201

© Sales - 93919 41702 © Service - 92811 51817

East Zone -2 PPS Motors Private Limited

Plot No. 614-623, Khata No 98, Mouza-Jiyalgora, G.T Road, KG Ashram, Govindpur, Dhanbad, Jharkhand - 828109

© Sales - 93919 41702 © Service - 93919 44690

North Zone PPS Motors Private Limited

3066/1, 3069/1, situated at NH-39, Nugarh Village, Post Kachani Tehsil, Singrauli, Madhya Pradesh, 486889

© Sales - 93919 41680 © Service - 77807 71251

Central Zone PPS Motors Private Limited

Plot No. C-20, Industrial Area, Chandrapur MIDC, Maharashtra, 442406

© Sales - 93919 41680 © Service - 92810 11745

West Zone PPS Motors Private Limited

Sy No 239, TP No 432, FP No 25, Shed No 10 and 11, Harikrupa Logistics Park, Behind shell petrol pump, Aslali, Ahmedabad,Gujarat 382427

© Sales - 91548 15775 © Service - 92810 11740



THE TAILORED OFFER

G500 XT 8X4 HEAVY TIPPER



DIMENSIONS

Wheel base	5475 mm
Overall length	9712 mm
Overall width	2600 mm
Overall height	3935 mm
Bogie distance	1450 mm

WEIGHTS

LADEN CHASSIS WEIGHT WITH BODY (As per CMVR)

Front axle	14000 kg
Rear axle	21000 kg
Total	35000 kg

ENGINE DC13 155 / 500 hp

Туре	Inline Engine
No. of Cylinders	6 Cylinders
Engine Displacement.	12.7 litres
Max. Power	500 Hp @ 1900 rpm
Max. Torque	2550 Nm @
	1000-1300 rpm
Injection system	XPI Injection System
Emission norms	Euro 6 / BS VI compliant
	with only SCR technolog

CLUTCH

Clutch Type	Single Dry Plate Clutch
Clutch Actuation	Electro hydraulic
Clutch plate diame	eter430 mm

GEARBOX GRS0935

Туре	Range Splitter gearbox
	with Overdrive
Gear shift	Scania Opticrusie with
program	lay shaft brake
No. of Gears	14F+2R
Crawler Gear	2 Numbers

ADBLUE AND FUEL TANK

AdBlue Tank Capacity	80 Litre
Fuel Tank Capacity	395 Litre

SUSPENSION FRONT

Туре	Parabolic
No. of leaf	5 no's with heavy
springs	duty hydraulic shock
ahs	orbers and anti roll bar

REAR

TypeT	rapezoidal extra wide
	bogie suspension
No. of leaf	8 no's with heavy
springs	duty Anti roll bar.

AXLES FRONT

Forged I beam reverse Elliot high mounted axle

REAR

Tandem bogie axle with Hub reduction Ratio 7.63:1

BRAKES

Dual circuit pneumatic drum brakes. Automatic Slack adjusters. ABS Off Road Mode. Traction control System. Manual and Automatic exhaust brake control with two step operation.



TYRES & RIMS

Wheel rim	6 Ton Capacity
Rim Size	8.5 X 24
Tyre Size	12 - 24, 20 PR
One complete spare wh	neel rim and tyre provided

ELECTRICAL SYSTEM

Voltage	2 X 12 V
Battery Capacity	150 Ah
Alternator	100 A

STEERING SYSTEM

Hydraulic power assisted	steering whee
Steering wheel dia	450 mm
Pneumatically Adjustable	Steering whe
Angle	0-52 degrees

CABIN CG 14L INTERIORS

Air Conditioned Cabin Engine hour meter Analogue Other features

- Fuel consumption display
- Scania Driver support system
- Auto engine shut down
- DPF filter Regeneration trigger
- DPF filter Clogging Indicator

EXTERIORS

Tinted Windscreen Heavy duty steel bumper -40 Ton 4 point suspension End outline Marker lamps

TIPPER BODY

U type Rock Body f	or Over burden*
Payload	38000 kg
Mean length	6191 mm
Width	2354 mm
Height	1642 mm
Body MaterialH	ardox 500 TUF/ Hardox 450
Tipping angle	48 Degrees
Hydraulic cylinder	Hyva FE169-4
Oil tank capacity	120 L

*Cladded body option available based on request and availability.

Note: In keeping with our policy of continual improvement, we reserve the right to modify the specifications without prior notice